

STREETDECK BEV | ELECTROLINER



Vehicle accessibility

- 1 or 2 door option
- Wheelchair access via electronic or manual ramp

Axle

- Front – ZF RL82 EC
- Rear – ZF AV133

Battery System

- 59Ah VDA PHEV2 modules (3P4S)
- Option of 3 or 4 String

Charge Time

- 340kWh – 2 ½ hours @ 150kW
- 454kWh – 3 hours @ 150Kw
- Up to 420kW Opportunity Charging / Pantograph Charging

EV Charging

- CCS2.0 Compliant Combo2 Socket
- 150kW or 300kW fast charge

Dimensions (MM / 10.6)

- Overall Length: 10582
- Overall Width: 2520
- Wheelbase: 5480
- Front Overhang: 2607
- Rear Overhang: 2495

Drivers & Passenger Saloon Seating

- High proportion of low-floor seating
- Range of Seat Models available to include option of seat belts for both driver and passengers.

Electric Traction

- Voith VEDS MD 280kW
- Torque – 2850Nm
- Max Speed – 2850rpm

Legislative compliance

- Built to NSSTA requirements
- ECWVTA approved

Optional Spec Features

Optional Spec Features include but not limited to the following:

- Air Conditioning (Drivers Cab)
- Air Conditioning (Passenger Saloon Cab)
- Branch Deflectors
- CCTV
- Digital Tachograph
- Drivers Cab Assault Screen
- Fire Suppression System
- Livery
- Luggage Racks
- Mirror Eye
- Seat Belts
- Seating Model Options
- Staircase Glazing
- Ticket Bin
- Tyre Brand Options
- USB Points
- Wi-Fi

Passenger Capacity

- Maximum Capacity: 3 String - 96 / 4 String - 88
- Maximum Seated Capacity: 3 String - 74 / 4 String - 74
- Maximum Standing Capacity: 3 String - 28 / 4 String - 20

Range

- 340kWh approximately 150miles of range
- 454kWh approximately 200miles of range

Safety & Support

- Daytime running lights as standard
- Ergonomic Drivers Area (ISO compliant)
- High centred mounted rear brake lights
- Standard Reversing Alarm
- Access to Wrightbus Parts & Service

Wheels & Tyres

- 275 / 70R x 22.5 Tubeless Tyre
- Choice of either Bridgestone, Continental, or Michelin



Fast charge time



Improved air quality



Best in class range



No kerbside emissions